

INCOMPARABLE DEEP CYCLE AGM BATTERY

LDC12-26H (12V26Ah)





CHARACTERISTICS

Item		Specifications
Voltage		12V
Dimension	Length	181.0mm (7.13inches)
	Width	76.5mm (3.01inches)
	Container Height	171mm (6.73inches)
	Total Height	171mm (6.73inches)
Approx Weight		6.9kg (15.2lbs)
Terminal		T15(M5)
Container Material		ABS
Capacity	20HR	26Ah
	5HR	24Ah
Operating Temp. Range	Discharge	-20~55°C (-4~131°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)

APPLICATIONS

- Electric motorcycle
- Electric bicycle
- Wheelchair



INCOMPARABLE DEEP CYCLE AGM BATTERY

LDC12-26H (12V26Ah)

GENERAL FEATURES

Stable initial capacity

- PAM/NAM amount optimization
- 4BS crystal paste mixing & curing technology
- Double layer separator technology
- Improved design electrolyte S.G.

Less water loss

- PAM/NAM amount optimization
- New PAM/NAM recipe introduced
- Rare earth alloy

Solve NAM sulphation

- Carbon boost technology
- Pre-sulfate technology

Improved PSoC cycling

- Carbon boost technology
- Mix carbon boost technology
- Targeting for higher level through carbon technology

Delay PAM softening and shedding

- Plate assembly pressure re-engineering
- 4BS crystal paste mixing & curing technology
- Higher paste density


Optimize electrolyte stratification

- Introduce AGM-GEL technology


Excellent deep cycle performance

- Plate assembly pressure re-engineering
- New PAM/NAM recipe introduced
- Gel electrolyte technology
- Rare earth alloy
- Double layer separator technology
- Lower acid filling temperature


Charging Profiles



Relationship of OCV and State Of Charge



Cycle Life in Relation to Depth Of Discharges



Self-discharge Characteristics

